

Dry Chemical Hand Portable Extinguishers

Features

- Meets or exceeds requirements of ANSI/UL 299 and 711, or ULC S504 or S508
- USCG approved with proper bracket
- Simple operation and maintenance
- Durable red powder paint finish
- Tough, glare-resistant, one-piece mylar nameplates
- Rechargeable
- Units are supplied with wall hanging bracket
- 2 1/2 and 5 lb units also available with vehicle bracket attached and packaged with extinguisher
- Large, easy-to-read pressure gauge
- Six-year limited warranty from date of delivery to original end-user purchaser

Applications

PYRO-CHEM dry chemical extinguishers are designed for protection of light and ordinary hazards. These compact and portable extinguishers are designed for commercial compliance market applications. All extinguishers are designed to fit most wall mounted storage cabinets. Typical applications include light manufacturing, warehousing, restaurants, office buildings, shop areas, auto repair shops, paint process areas, welding areas, machinery, apartment buildings, parking garages, aircraft servicing areas, material handling vehicles, and many others.

Description




1. Shells are produced by a cold deep draw process which yields a seamless steel cylinder with a high tensile strength.
2. Unique pre-treatment of the raw low carbon steel not only consists of a cleaning process, but also applies a special lubricant which helps keep the interior and exterior shell surfaces scratch free.
3. The collar and specially pre-formed bottom enclosure are MIG welded to produce a smooth, high integrity weld.
4. Extinguisher shells are 100% factory air tested in excess of 600 psi (41.4 bar), 375 psi (26 bar) for 2 1/2 lb units.
5. The powder paint process is superior to conventional liquid based paint systems in its ability to resist blistering, cracking, fading, chipping, and corrosion.
6. Before the extinguisher shells are painted, they are surface treated with a blasting or phosphate bonding process. This enhances the paint adhesion and corrosion resistance.



008118

7. The specially formulated powder paint is electrostatically applied and oven cured to help ensure complete coverage and uniform paint thickness.
8. Easy grip extinguisher handles are designed for maximum portability, allowing operators to fight the fire without removing work gloves.
9. Extinguisher valve bodies are made from a durable extruded aluminum alloy.
10. Completed valve assemblies feature plated steel valve stems which contain o-ring and seat material compatible with the agent to provide reliable performance and long life.
11. Rugged all-steel pick-up tubes help provide proper and dependable agent flow through the valve body.
12. Extinguishers have large, color-coded pressure gauges which provide a quick visual indication of unit readiness.
13. Large 1 1/4 in. (32 mm) diameter coated steel ring pins are utilized and held in place by a visual seal to help prevent accidental discharges. **Note:** Smaller ring pins for 2 1/2 lb units are stainless steel.
14. One piece, multilingual, color-coded mylar label with easy-to-read pictograms provides the user with step-by-step operating instructions and the hazard classes for which the extinguisher was designed. Label also contains useful recharge, maintenance, inspection, operating temperature, HMIS and model information.
15. Large, easy-to-scan bar coded model and UL/ULC serial numbers simplify inspection and maintenance record keeping.
16. Valve subassemblies are 100% tested for functionality before final assembly.
17. Extinguishers are vacuum-filled at the factory to precise filling tolerances.
18. 100% leak tested utilizing mass spectrometry technology at pressures of 195 psi (13.4 bar), and 125 psi (8.6 bar) for 2 1/2 lb units.

Specifications

Dry Chemical Extinguishers	2 1/2 lb	5 lb		
	 009708	 008110	 008112	
Model	PC2.5SVBABC-1/ PC2.5SABC-1	PC05SABC+2/ PC05SVBABC+2	PC05SABC-1/ PC05SVBABC-1	PC05SPK-1
Extinguisher Part No. (except Canada)¹	553627/ 553624	553716/ 553717	553710/ 553709	553712
Extinguisher Part No. (Canada)²	553633/ 553630	553718/ 553719	553708/ 553707	553711
Bracket Part No.	24610	429146	429146	429146
Agent Capacity	2 1/2 lb (1.13 kg) ABC	5 lb (2.27 kg) ABC	5 lb (2.27 kg) ABC	5 lb (2.27 kg) PK
UL/ULC Rating	1-A:10-B:C	3-A:40-B:C	3-A:10-B:C	60-B:C
Coast Guard Classification	Type B, C, Size I	Type A, Size II Type B, C, Size I	Type A, Size II Type B, C, Size I	Type B, C, Size I
Discharge Time	9 seconds	14 seconds	15 seconds	17 seconds
Maximum Effective Range	11 ft (3.4 m)	14 ft (4.3 m)	14 ft (4.3 m)	16 ft (4.9 m)
Operating Temperature Range	-65 °F to 120 °F (-54 °C to 49 °C)	-65 °F to 120 °F (-54 °C to 49 °C)		
Agent Flow Rate	0.31 lb/sec (0.14 kg/sec)	0.36 lb/sec (0.16 kg/sec)	0.37 lb/sec (0.17 kg/sec)	0.30 lb/sec (0.14 kg/sec)
Charged Weight (with agent)	5 lb (2.27 kg)	9 lb, 1 oz (4.12 kg)	8 lb, 13 oz (4.0 kg)	9 lb, 1 oz (4.12 kg)
Dimensions:				
Height	13 3/4 in. (349 mm)	16 3/4 in. (425 mm)		
Width	5 1/4 in. (133 mm)	8 1/2 in. (216 mm)		
Depth	3 3/8 in. (86 mm)	4 7/16 in. (113 mm)		
Fire Suppression Capability³				
Operator:				
Novice	10 ft ² (0.93 m ²)	40 ft ² (3.7 m ²)	10 ft ² (0.93 m ²)	60 ft ² (5.6 m ²)
Experienced	25 ft ² (2.3 m ²)	100 ft ² (9.3 m ²)	25 ft ² (2.3 m ²)	150 ft ² (13.9 m ²)

¹ UL Listed. English/Spanish nameplates.

² ULC Listed. English/Canadian French nameplates.

³ Underwriters Laboratories classifies a "novice operator" as one who has little or no experience in operating a fire extinguisher.

10 lb



008402

008678

20 lb



008118

PC10SABC+1	PC10SPK-1	PC10SBC-1	PC20ABC+2	PC20PK-1	PC20BC-1
553501	553555	553549	553369	553081	552949
553507	553558	553552	553372	553080	552948
435793	435793	435793	30937	30937	30937
10 lb (4.54 kg) ABC	10 lb (4.54 kg) PK	10 lb (4.54 kg) BC	20 lb (9.07 kg) ABC	20 lb (9.07 kg) PK	20 lb (9.07 kg) BC
4-A:80-B:C	80-B:C	60-B:C	10-A:120-B:C	120-B:C	80-B:C
Type A, Size II Type B, C, Size II	Type B, C, Size II	Type B, C Size II	Type A, Size II Type B, C, Size III	Type B, C, Size III	Type B, C, Size III
21 seconds	22 seconds	19 seconds	28 seconds	30 seconds	21 seconds
20 ft (6.1 m)	20 ft (6.1 m)	16 ft (4.9 m)	22 ft (6.7 m)	22 ft (6.7 m)	22 ft (6.7 m)
-65 °F to 120 °F (-54 °C to 49 °C)			-40 °F to 120 °F (-40 °C to 49 °C)		
0.52 lb/sec (0.24 kg/sec)	0.46 lb/sec (0.21 kg/sec)	0.59 lb/sec (0.27 kg/sec)	0.73 lb/sec (0.33 kg/sec)	0.67 lb/sec (0.30 kg/sec)	0.99 lb/sec (0.45 kg/sec)
17 lb, 0 oz (7.73 kg)	17 lb, 14 oz (8.13 kg)	17 lb, 14 oz (8.13 kg)	32 lb, 2 oz (14.60 kg)	32 lb, 2 oz (14.60 kg)	32 lb, 2 oz (14.60 kg)
20 1/2 in. (520 mm) 8 1/4 in. (210 mm) 5 1/4 in. (135 mm)			22 1/2 in. (572 mm) 9 1/2 in. (241 mm) 7 7/32 in. (183 mm)		
80 ft ² (7.4 m ²) 200 ft ² (18.6 m ²)	80 ft ² (7.4 m ²) 200 ft ² (18.6 m ²)	60 ft ² (5.6 m ²) 150 ft ² (13.9 m ²)	120 ft ² (11.1 m ²) 300 ft ² (27.9 m ²)	120 ft ² (11.1 m ²) 300 ft ² (27.9 m ²)	80 ft ² (7.4 m ²) 200 ft ² (18.6 m ²)

Approvals: DOT, USCG (All Models with proper bracket)

Hydrostatic Test Requirement: Once every 12 years (All Models)

Note: VB denotes with vehicle bracket

Description (Continued)

19. Injection molded nozzle tips are designed to tight specifications and maximize the suppression capabilities of the particular model and agent.
20. Extinguishers are shipped from the factory in individual recyclable corrugated cardboard cartons. Designed and field tested to help ensure your extinguishers arrive undamaged and ready for operation. The glued one-piece cartons have carrying handles and a pressure gauge inspection port.
21. All extinguisher cartons are properly labeled according to the latest DOT regulations for ease of shipping in the field.
22. PYRO-CHEM dry chemical suppressing agents are manufactured from high quality raw materials and are carefully blended to meet stringent performance specifications. These agents are then tested to be free-flowing, water repellent and electrically nonconductive.
23. As a final quality control step, extinguishers are randomly sampled for performance testing, which includes weight percent discharge and discharge times.

Agent

ABC – A monoammonium phosphate-based agent for use on Class A (wood, paper, cloth) and Class B (flammable liquids and gases) fires, and Class C (electrical) conductivity.

PK – A potassium bicarbonate-based agent which is the most effective agent for knock-down of Class B (flammable liquids and gases) fires and Class C (electrical) conductivity.

BC – A sodium bicarbonate-based agent for use on Class B (flammable liquids and gases) fires and Class C (electrical) conductivity.

Ordering Information

For fire protection assistance, see your nearest authorized PYRO-CHEM distributor or contact your PYRO-CHEM sales representative.

Note: The converted metric values in this document are provided for dimensional reference only and do not reflect an actual measurement.

PYRO-CHEM, and the product names listed in this material are marks and/or registered marks. Unauthorized use is strictly prohibited.